

implementation of an effective combination of erosion and sediment control BMPs from Table 7 and/or Table 8 of this Order (where applicable) to prevent erosion and sediment loss, and the discharge of construction wastes.

**Table 7. Minimum Set of BMPs for All Construction Sites**

<b>Site Management</b>	Housekeeping
<b>Erosion Controls</b>	Scheduling
	Preservation of Existing Vegetation
	Wind erosion controls
<b>Sediment Controls</b>	Perimeter controls (e.g. Silt Fence, Sandbag Barriers, etc.)
	Stabilized Construction Site Entrance/Exit
<b>Non-Stormwater Management</b>	Water Conservation Practices
	Dewatering Operations
<b>Waste Management</b>	Material Delivery and Storage
	Stockpile Management
	Spill Prevention and Control
	Solid Waste Management
	Concrete Waste Management
	Sanitary/Septic Waste Management

**Table 8. Minimum Required BMPs for Roadway Paving or Repair Operation (For Private or Public Projects)**

<b>1</b>	Restrict paving and repaving activity to exclude periods of rainfall or predicted rainfall unless required by emergency conditions.
<b>2</b>	Install gravel bags and filter fabric or other equivalent inlet protection at all susceptible storm drain inlets and at manholes to prevent spills of paving products and tack coat.
<b>3</b>	Prevent the discharge of release agents including soybean oil, other oils, or diesel to the stormwater drainage system or receiving waters.
<b>4</b>	Minimize non stormwater runoff from water use for the roller and for evaporative cooling of the asphalt.
<b>5</b>	Clean equipment over absorbent pads, drip pans, plastic sheeting or other material to capture all spillage and dispose of properly.
<b>6</b>	Collect liquid waste in a container, with a secure lid, for transport to a maintenance facility to be reused, recycled or disposed of properly.
<b>7</b>	Collect solid waste by vacuuming or sweeping and securing in an appropriate container for transport to a maintenance facility to be reused, recycled or disposed of properly.
<b>8</b>	Cover the "cold-mix" asphalt (i.e., pre-mixed aggregate and asphalt binder) with protective sheeting during a rainstorm.
<b>9</b>	Cover loads with tarp before haul-off to a storage site, and do not overload trucks.
<b>10</b>	Minimize airborne dust by using water spray or other approved dust suppressant during grinding.
<b>11</b>	Avoid stockpiling soil, sand, sediment, asphalt material and asphalt grindings materials or rubble in or near stormwater drainage system or receiving waters.
<b>12</b>	Protect stockpiles with a cover or sediment barriers during a rain.

**b. Construction Site Inspection.** Inspect construction sites as needed based on the evaluation of the factors that are a threat to water quality. In evaluating the threat to